

A wide-angle photograph of a modern shopping mall hallway. The floor is highly reflective, showing the ceiling lights and the storefronts. On the left, there are glass storefronts for various shops, including one with a purple sofa. In the center, a mannequin is visible in a shop window. On the right, another shop window displays several mannequins wearing clothing. The ceiling is white with recessed lighting.

GREE
AIR CONDITIONER

Air Curtain



Find out more at www.greeac.com.au

Why choose an Air Curtain?

Air Curtains help sustain a healthy working environment whether cooling, heating or ambient conditions for a comfortable climate for customers and employees.

An air curtain allows for open door trading in retail outlets offering uninterrupted access to the public.

Easy to install and easy to maintain, air curtains offer a simple and cost effective solution to maintain an inviting climate in any working or retail space.



The new advantage in the energy battle



Energy Savings

By providing environmental separation between indoor and outdoor temperatures, recent studies have shown that by fitting an air curtain you can save up to 33% of your HVAC running costs. Pay back for some commercial applications can be as little as 21 weeks.

Improved Indoor Air Quality

Gree Air Curtains prevent dust, dirt and fumes from infiltrating and contaminating indoor areas.

Lower Construction Costs

With the use of Gree Air Curtains architects can design a building without vestibules, which can save on construction costs and provide more retail floor space.

Improved Working Conditions

Keeps out ambient air at door openings and re-circulates conditioned air from ceiling to floor for more comfortable working conditions.

Features

Optimized cross flow fan with a high performance motor.

Anti corrosion protection thanks to a two sided electro galvanised metal case.

Integrated electric components for easy maintenance.

Micro processor control with greater reliability and a long service life.

High performance cross flow fan blade with 3D optimized streamlining.

Remote controlled operation.



FM-1.25-9-K

Performance

Power Supply: 220~230/50V/Hz

Power Input: 110W

Airflow Volume: 1200l/s

Airflow Velocity: 8m/s

Min Install Height: 2.5m

Max Install Height: 3.0m

Sound Pressure Level (H/L): 59/56dB(A)

Dimensions (HxWxD)

External Dimensions: 900x215x193mm

Net Weight: 16kg

FM-1.25-1.2-K

Performance

Power Supply: 220~230/50V/Hz

Power Input: 140W

Airflow Volume: 1650l/s

Airflow Velocity: 8m/s

Min Install Height: 2.5m

Max Install Height: 3.0m

Sound Pressure Level (H/L): 61/56dB(A)

Dimensions (HxWxD)

External Dimensions: 1200x215x193mm

Net Weight: 20kg

Features



Quiet Design



Compact Design



Easier
Maintainability



Z1403



For Installation and Sales:



For Parts and Warranty:

 **GREE**
AIR CONDITIONER

www.greeac.com.au

1800 GREE 4 ME
1800 4733 4 63